



REAR ELEVATION



FRONT ELEVATION

Property of TK Constructors, Inc.

<h1 style="margin: 0;">TK CONSTRUCTORS</h1> <h2 style="margin: 0;">GATLINBURG</h2>	<p>DATE: October 25, 2012</p> <p>JOB NO.: 111-12-0126</p>
<p>CONSTRUCTORS</p>	<p>ADDENDUM 1,4</p> <p>VER: 05100933A</p> <p>DRAWING BY: SES</p> <p>SCALE: 1/8 IN.=1 FT.</p>
<p>PAGE NO.: 1B</p>	

FLOOR PLAN

TOTAL LIVING SQ.FT.	1,314
GARAGE	410
TOTAL SQ.FT.	1,724
EXCLUDING PORCH	90

ANDERSEN WINDOW SCHEDULE - 200 SERIES -	
ANDERSEN MODEL NO.	R.O. SIZE
3030	36" x 36"
3040	36" x 48"
3049*	36" x 57"
3056*	36" x 66"
3060*	36" x 72"
3049 MULL*	73" x 57"
3056 MULL*	73" x 66"
3060 MULL*	73" x 72"
ANDERSEN SLIDING DOOR R.O. 72 3/4" x 82 1/8"	
3'-0" FRONT DOOR R.O. 38 3/8" x 82 1/2"	
3'-0" FRONT DOOR WITH (1) SIDELITE R.O. 51 1/8" x 82 1/2"	
3'-0" FRONT DOOR WITH (2) SIDELITES R.O. 65 3/8" x 82 1/2"	
R.O. FOR BI-FOLD DOORS USING DRYWALL JAMB FACING = 1 1/4" + DOOR SIZE x (81 1/2")	
R.O. FOR BYPASS DOORS USING DRYWALL JAMB FACING MAKE SAME AS BOTH DOORS ADDED TOGETHER	
ALL INTERIOR DOORS SIZE + 2" TO WIDTH x 82 1/2" HIGH	
R.O. POCKET DOOR (2x DOOR WIDTH + 1") x 85" HIGH	

* - DENOTES OPENING MEETS
EGRESS REQUIREMENTS

